



CsIII

Cesium Frequency Standard Model 4310B

KEY FEATURES

- Third Generation Cesium Technology
- 2U Compact Rack Mount
- AC & DC inputs
- Remote Monitoring & Control
- 5 & 10MHz Outputs
- 1PPS Sync input
- 1PPS Output
- 30 Minute Warm-Up to Full Specifications
- <30 lbs

OPTIONAL FEATURES

- T1/E1 Outputs
- Portability Kit

OVERVIEW

Symmetricom's CsIII is a lightweight, compact, economical cesium frequency standard. The technology developed for the CsIII is an evolutionary step forward in the quest for higher stability, lower phase noise and longer life. An ever-increasing base of demanding users in communications, timing, synchronization and other applications take advantage of this performance.

The CsIII is configured with 5 and 10MHz sinewave outputs, a 10MHz TTL output a 1PPS sync input and a 1PPS timing output. All monitoring and control of the unit is done via the serial interface and Symmetricom's proprietary Monitor3 software.

Packaged in a 2U, 19-inch rack mounted chassis, the CsIII weighs less than 30 lbs. An optional portability kit and T1/E1 synthesizer are available for added functionality and versatility.

The CsIII comes standard with a 2-year electronics warranty and 12-year tube warranty.

The CsIII is ideal for SATCOM, Calibration, Metrology and many other Test & Measurement applications that required cesium stability and accuracy.



CsIII Cesium Frequency Standard

CsIII Specifications

ELECTRICAL SPECIFICATIONS

- Frequency outputs

Frequency:	1 each 5 MHz and 10 MHz
Format:	Sine
Amplitude:	1 Vrms
Harmonic:	<-40dBc
Non harmonic:	<-80dBc
Connector:	BNC
Load impedance:	50Ω
Location:	rear panel

Frequency:	10 MHz
Format:	TTL
Amplitude:	>2.2V
Load impedance:	50Ω
Location:	rear panel
Connector:	BNC

- Timing outputs

Format:	1PPS
Amplitude:	>3.0V into 50Ω (TTL compatible)
Pulse width:	20μs positive pulse
Rise time:	<5ns
Jitter:	<1ns rms
Connector:	BNC
Load impedance:	50Ω
Location:	rear panel

- Timing inputs

Sync input:	1PPS
Amplitude:	>3.0V into 50Ω (TTL compatible)
Pulse width:	20μs positive pulse
Rise time:	<5ns
Jitter:	<1ns rms
Connector:	BNC
Load impedance:	50Ω
Location:	rear panel

REMOTE SYSTEM INTERFACE AND CONTROL

RS-232-C (DTE Configuration)

Complete remote control and interrogation of all instrument functions and parameters

Connector	
RS-232-C:	9-pin male rectangular D subminiature type
Location:	rear panel
Alarm (Relay):	9-pin female rectangular D subminiature type
Location:	rear panel

- Performance parameters

Accuracy:	±1.0E-12
Warm-up time (typical):	30 minutes
Reproducibility:	±2.0E-13
Settability	
Range:	±1.0E-9
Resolution:	1.0E-15
Control:	Via RS-232 port

- Stability

Averaging Time(s)	Allan Deviation
1	<1.2E-11
10	<8.5E-12
100	<2.7E-12
1,000	<8.5E-13
10,000	<2.7E-13
100,000	<8.5E-14
floor	<5.0E-14

- SSB Phase noise

Offset (Hz)	5MHz output
1	<-95dBc
10	<-130dBc
100	<-145dBc
1,000	<-155dBc
10,000	<-155dBc
100,000	<-160dBc

ENVIRONMENTAL & PHYSICAL SPECIFICATIONS

- General Environment

Temperature	
Operating:	0°C to 50°C
Non-operating:	-40°C to 70°C
Humidity:	95% up to 50°C
Magnetic field:	0 to 2 gauss
Altitude (operating):	0 to 50,000 feet

- AC Power requirements

Operating voltage:	100 to 240 VAC +/-10%
Frequency:	47 to 63 Hz
Power	

Operating:	<65W
Warm-up:	<90W

- DC Power requirements

22 to 36 VDC
36 to 75 VDC
30W 1.3A @ 24V (Operating)
65W 2.7A @ 24V (Warm Up)

- Dimensions/Weight

Height:	3.50" (89.9mm)
Width	
Front panel:	19.00" (483mm)
Instrument	17.31" (440mm)
Depth:	15.0" (381mm)
Weight:	<30lbs (13.5kg)
MTBF:	>130,000 hrs.

ORDERING INFORMATION

- 24VDC, 12 Yr. Warranty
- 48VDC, 12 Yr. Warranty

Part No.

14534-110
14534-109



CsIII connections



SYMMETRICOM, INC.
2300 Orchard Parkway
San Jose, California
95131-1017
tel: 408.433.0910
fax: 408.428.7896
info@symmetricom.com
www.symmetricom.com